



Nitrile

Provides sturdy coverage for demanding applications



FEATURES AND BENEFITS:

Exceptional Protection

The Microflex Supreno® SE offers an advanced barrier protection against contaminants due to its lower acceptable pinhole rates. Its 0.65 Acceptance Quality Limit for pinholes help set a new standard for protection.

Increased Productivity

Non-stick properties are built into the glove formulation to create a resistance to tape or adhesives, and to assist workers with improved efficiency and speed.

Secure and Confident Grip

Textured fingers ensure strong, efficient grip and maximum worker protection.

Effortless Donning and Doffing

Polymer coating assures easy donning to help protect workers in fast-paced environments.

Protection from Type 1 Allergies

Constructed without natural rubber latex materials or powder, to help protect from allergies, skin irritation and dryness.

Industries

- Automotive
- Chemical
- Healthcare
- Laboratory
- Law Enforcement
- Manufacturing

Applications

- Crime scene evaluation
- Patient examinations
- Analytical testing
- Assembly and inspection
- Electronics
- Food processing
- Glass manufacturing
- Laboratory analysis and testing
- Light assembly tasks
- Maintaining equipment & instruments
- Paint and spray shops
- Patient examinations
- Pharmaceutical manufacturing
- Preparing pharmaceutical products
- Printing industry
- Protection from blood and other bodily fluids

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

	SUPRENO® SE
Material	Nitrile
Color	Blue
Glove Design	Ambidextrous, Powder-Free, Chlorinated, Polymer Coated, Textured Fingers
Cuff	Beaded Cuff
Audit Standards	ISO 13485
Regulatory Compliance	ASTM D6319, US QSR/FDA 510(K) MEDICAL (EXAMINATION) GRADE, COMPLIANT WITH U.S. FOOD CONTACT REGULATIONS
Packaging	100 gloves per dispenser, 10 dispensers per shipper carton, 1000 gloves per shipper carton.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia

PHYSICAL PROPERTIES:

	TYPICAL VALUES					TESTING METHOD
	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	
Length (mm)	245	245	245	245	245	ASTM D3767/EN 420
Average Palm Width (mm)	75	86	98	108	115	
Freedom from Holes (Inspection level I)	0.65 AQL					ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm : 0.11) / (mil : 4.3)					ASTM D3767/EN 420
	BEFORE AGING		AFTER AGING			
Ultimate Tensile Strength	30 Mpa		30 Mpa		ASTM D 412-06a	
Elongation at Break (%)	> 500		> 400		ASTM D 412-06a	
Force at break (N)	10		11		EN 455-2	

ORDERING INFORMATION:

	SIZE	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL
SUPRENO® SE	REORDER NO.	SU-690-XS	SU-690-S	SU-690-M	SU-690-L	SU-690-XL

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

For additional information visit us at www.ansell.com, or call us at 1-877-750-6110

Ansell
111 Wood Avenue South
Suite 210
Iselin, NJ 08830
USA

Ansell
105 Lauder
Cowansville, QC J2K 2K8
Canada

