

Oxygen Pressure Regulators

Built to Last in the Rugged Emergency Environment



L270-220

The Life Support Products series of all-brass body oxygen pressure regulators provides enhanced safety features and a greater number of flow selections for the EMS professional.

The uni-body construction is designed to strengthen the regulator, minimize potential leak paths, and prevent breakage of the yoke cylinder connection assembly. For additional safety, inlet filters provide gas filtration down to 20 microns. Standard LSP regulators have a 5-year warranty.

LSP regulators offer 12 flow positions ... more flow selections than ever before. Equipped with up to two DISS check valves, LSP regulators provide regulated pressure and flow for the operation of two demand valves, or one demand valve and one aspirator, or any pneumatically-powered ventilator. A DISS or hose barb adjustable flow outlet permits attachment of a disposable mask, cannula, or bag mask device. All three outlet configurations may be operated simultaneously.

The Rhino™ oxygen regulator is virtually unbreakable. This oxygen pressure regulator features an all-brass uni-body construction designed to strengthen the regulator, prevent yoke damage and regulator leakage, and protect the flow selector knob from accidental adjustment. The Rhino regulator also has a unique integrated aluminum shroud and lens cover that shelters the gauge from breakage and contamination, and is available in a choice of five colors.

A 20 micron sintered bronze gas inlet filter provides gas filtration and additional protection against contamination. Rhino regulators are available with up to two male DISS oxygen check valves and different flow ranges delivered through a hose barb outlet. The Rhino regulator has a 10-year warranty.



L370-220-R

Key Features

- Uni-body construction designed to prevent yoke breakage and regulator leakage, and provide complete protection to the constant flow selector knob
- Nickel-plated brass body is fire resistant and able to withstand corrosive materials, the marine environment, and harsh weather conditions
- Sintered bronze high-pressure inlet filter for enhanced protection against contamination
- Compact break-resistant low profile contents gauge
- Large easy to read flow rate numbers
- Two body designs: yoke inlet for small cylinders, and nut and nipple inlet for large cylinders
- Hose barb or DISS outlet connection for oxygen supply to patient
- 10-year warranty on Rhino regulators, with patented protective shroud

Oxygen Pressure Regulators



L270-250



L270-220



L106-260



L280-220



L370-220-R

SPECIFICATIONS

Supply Pressure: 500 to 2200 psi

Outlet Pressure: High flow outlets: 40 to 60 psi at 500 to 2200 psi inlet pressure

Flow Capacity: High flow outlets: 125 lpm minimum single or combined flow with 500 psi inlet pressure

Constant flow outlet selections:

0-15 lpm: 0, .5, 1, 1.5, 2, 3, 4, 5, 6, 8, 10, 15

0-25 lpm: 0, .5, 1, 2, 4, 6, 8, 10, 12, 15, 20, 25

Filter: 25 micron sintered bronze

Safety Relief Pressure: 75-125 psi

Operating Temperature: -30° F to 125° F

Storage Temperature: -20° F to 120° F

Materials: Body - nickel-plated brass; knob - anodized aluminum; outlets - nickel-plated brass; internal parts - brass, stainless steel, Viton®, silicon, and Teflon®

All LSP brass oxygen regulators are laser-engraved with the LSP logo, model number, date code and bar code to assist in preventing loss and tracking for routine maintenance.

ORDERING INFORMATION

Yoke Pin Indexed CGA 870 Regulators

L270-230 0-15 lpm, with gauge, 2 check valves, hose barb outlet

L270-260 0-15 lpm, with gauge, hose barb outlet

L270-220 0-25 lpm, with gauge, 2 check valves, hose barb outlet

L270-220-CE 0-25 lpm, with gauge, 2 check valves, hose barb outlet

L270-250 0-25 lpm, with gauge, hose barb outlet

L370-220* 0-25 lpm, with gauge, 2 check valves, hose barb outlet

L370-250* 0-25 lpm, with gauge, hose barb outlet

DISS Fitting CGA 540 Regulators

L106-260 Fixed flow, with gauge, 2 check valves

L280-220 0-25 lpm, with gauge, 2 check valves, hose barb outlet



L270-220-CE



EMERGO EUROPE
Molenstraat 15
2513 BH, The Hague
The Netherlands

*Rhino™ Regulators: Add color choice to the model number for your choice of gauge shroud color.
A = Aluminum, B = Blue, G = Green, R = Red, GL = Gold.
Example: L370-220-R

Additional models are available. For information about our complete line of oxygen regulators, contact an Allied healthcare Products Customer Service Representative.



Allied Healthcare Products, Inc. ▪ 1720 Sublette Avenue ▪ St. Louis, MO 63110 USA
314/771-2400 ▪ 800/444-3954 ▪ FAX: 314/771-0650 ▪ www.alliedhpi.com

U.S.
Toll Free: 800/444-3940
FAX: 800/477-7701

Canada & Mexico
Toll Free: 800/446-0552
FAX: 800/246-6201

International
Telephone: 314/268-1683
FAX: 314/771-5183

ISO 13485: 2003

©Allied Healthcare Products, Inc.®

All specifications are nominal and subject to change without notice.

Form 90-00-0002
Rev. January 2014