



eitan
medical
sapphire



QuadMed, Inc.

sapphire™ Multi-Therapy Infusion Pump

FOR EMS



When every second counts,
Sapphire Multi-Therapy IV infusion pump delivers.
Even under the most demanding conditions



We have designed Sapphire to be small, lightweight & sturdy

the perfect partner for any pre-hospital clinician, no matter the environment

Emergency Responder Ready Features

- + Intuitive user interface
- + Highly customizable, with versatile programming options
- + Fast setup and programming
- + Extensive drug library capability with simple search feature
- + Half Set available
- + Approved for air and ground transport*
- + Multiple mounting and carrying solutions**
- + Durable design with a small footprint
- + Long battery life
- + Reliable and cost-effective

* IEC 60601-1-12 - Requirements for medical electrical equipment and medical electrical systems intended for use in the emergency medical service environment.

** SAE J3043 - J2917 Frontal Impact | J3044 Rear Impact | J2956 Side Impact

Key specifications & features

Dimensions

143 x 96 x 49 mm (5.63 x 3.78 x 1.93 in.) (H x W x D)

Weight (excluding battery)

418 g (14.7 oz.)

Indications

Intravascular, subcutaneous, intra-arterial, epidural

Indicated Use

The pump is intended to be used by licensed health care professionals in a clinical environment, home users in an ambulatory environment and in pre-hospital medical air and ground transportation

EMS Standard

IEC 60601-1-12 - Requirements for medical electrical equipment and medical electrical systems intended for use in the emergency medical services environment.

Drug Library

Holds up to 40 different clinical care areas and 1,000 drugs per area

Infusion device

Volumetric, peristaltic

Delivery Modes

Continuous, PCA, Intermittent, Multi-Step, TPN, Epidural

Accuracy

±2.5% under normal conditions (per IEC60601-2-24 standard)

Flow Rate

0.1 - 999 mL/h
0.1 - 99.9 mL/h in increments of 0.1 mL/h
100 - 999 mL/h in increments of 1 mL/h

Volume (VTBI)

0.1 - 9999 mL in increments of 0.1 mL

Power Supply

100 - 240V 50-60 Hz, 0.6A

Battery Type

Rechargeable Li-Ion battery 7.4V, 1960 mA/h

Battery Life

24 hrs @ 125 mL/h Recharge time: up to 6 hrs

Downstream occlusion

Up to 17.4 PSI (1.2 bar or 900 mmHg)

Temperature

Operating Temperature: +5° (41°F) to 40°C (104°F)
Storage/Transit Temperature: -40°C (-40°F) to +70°C (+158°F)



Make a difference when Every Second Matters

We know that in an emergency, every second counts. Sapphire's simple single hand cassette insertion, quick set-up, and intuitive workflows can improve response time so you can focus on saving lives

Overcome harsh Conditions

We understand life in a prehospital environment is filled with surprises and challenges. Sapphire is a durable and sturdy performer. Built to withstand drops and bumps, as well as splashing fluids, with a touch screen that can be operated even when wet, giving you the confidence needed to **initiate an infusion anytime, anywhere**

Respond with Precision

We understand the unique needs of adults, pediatrics, and other populations. Sapphire can safely manage infusions for each of your patient sets with a wide flow rate range, industry-leading flow rate accuracy, and exceptional flow continuity. Preset programs, can be configured to **accommodate a variety of protocols and streamline pump programming**

Control your Investment

We know the costs of infusion pump maintenance and we offer a variety of Extended Service Programs to meet the needs of your organization. We can provide the tools and training to complete maintenance activities independently, **minimizing downtime and reducing operational costs**





QuadMed, Inc Contact information:

sales@quadmed.com

904-880-2323

Manufactured By:

Eitan Group North America

65 Enterprise 3rd Floor Aliso Viejo, CA 92656, USA

Technical Service Contact Information:

service@eitanmedical.com



Q Core Medical Ltd. is the manufacturer of Sapphire products.